



crealco

EVOLUTION<sup>TM</sup>



BOTTOM-HUNG OPEN-IN WINDOW



A product of

**WISPECO**  
Aluminium



## FEATURES

- Bottom hung open in window system.
- Can be glazed from the inside and from the outside.
- Open out top hung or side hung vents also available.
- Cottage pane configurations are available.

## GLAZING

- Beaded both sides.
- Glass thickness from 4mm to 6.38mm

## GASKETS & SEALS

- Standard Crealco colour coded wedges.
- Crealco approved seals.

## FINISH

- Available in anodized finish.
- Available in Crealco standard colours.

## HARDWARE

- Approved Crealco friction stays.
- Approved Crealco window handles.



Ring pull catch doubles up as a handle



INSIDE

OUTSIDE

**SASH LIMITATIONS**

WIDTH	HEIGHT
850mm	700mm

This brochure must be read in conjunction with the Installation, Cleaning & Maintenance Guidelines for the relevant system.  
The manuals must also be used in conjunction with the design and cutting lists from the latest version of StarFront.



## TEST RESULTS

## MECHANICAL PERFORMANCE RESULTS - SANS 613

DESCRIPTION	RESULTS
NEGATIVE PRESSURE	Passed 1500 Pa
POSITIVE PRESSURE	Passed 1500 Pa
WATER PENETRATION	Passed 300 Pa
STRUCTURAL	Passed 2250 Pa

## APPLICATIONS

crealco Windows	HOME	MANSION	MALL	TOWER
Swift 28 window	✓			
Swift 30.5 window	✓			
Evolution window	✓	✓	✓	
Swift 34 window		✓	✓	
Swift 36 window		✓	✓	✓
Clipp 44 window			✓	
Edge thermal break window		✓	✓	✓
Serene window		✓	✓	✓

To find your nearest Crealco Distribution Partner, please visit the Crealco website at :

[www.crealco.co.za](http://www.crealco.co.za)

This brochure must be read in conjunction with the Installation, Cleaning & Maintenance Guidelines for the relevant system.  
The manuals must also be used in conjunction with the design and cutting lists from the latest version of StarFront.